


Geberit PE Reduktion exzentrisch, kurz



Beispielbild

EIGENSCHAFTEN

- Exzentrisch

TECHNISCHE DATEN

Werkstoff

PE-HD

Art.-Nr.	NPK-Nr.	d ₁ ø mm	d ₁ ø mm	A cm	H cm	h cm	h ₁ cm	K cm
361.558.16.1	312.314	50	40	0.5	8	3.5	3.7	2
363.558.16.1	312.315	56	40	0.8	8	3.5	3.7	2
363.561.16.1	312.315	56	50	0.3	8	3.5	3.7	2
364.558.16.1	312.316	63	40	1.2	8	3.5	3.7	2
364.561.16.1	312.316	63	50	0.7	8	3.5	3.7	2
364.566.16.1	312.316	63	56	0.4	8	3.5	3.7	2
365.558.16.1	312.317	75	40	1.8	8	3.5	3.7	2

Art.-Nr.	NPK-Nr.	d _ø mm	d1, ø mm	A cm	H cm	h cm	h1 cm	K cm
365.561.16.1	312.317	75	50	1.3	8	3.5	3.7	2
365.566.16.1	312.317	75	56	1	8	3.5	3.7	2
365.571.16.1	312.317	75	63	0.6	8	3.5	3.7	2
366.561.16.1	312.318	90	50	2	8	3.5	3.7	2
366.566.16.1	312.318	90	56	1.7	8	3.5	3.7	2
366.571.16.1	312.318	90	63	1.3	8	3.5	3.7	2
366.576.16.1	312.318	90	75	0.8	8	3.5	3.7	2
367.558.16.1	312.321	110	40	3.4	8	3.5	3.7	2
367.561.16.1	312.321	110	50	2.9	8	3.5	3.7	2
367.566.16.1	312.321	110	56	2.6	8	3.5	3.7	2
367.571.16.1	312.321	110	63	2.2	8	3.5	3.7	2
367.576.16.1	312.321	110	75	1.6	8	3.5	3.7	2
367.581.16.1	312.321	110	90	0.9	8	3.5	3.7	2

<i>Art.-Nr.</i>	<i>NPX-Nr.</i>	<i>d_ø</i> mm	<i>d1, ø</i> mm	<i>A</i> cm	<i>H</i> cm	<i>h</i> cm	<i>h1</i> cm	<i>K</i> cm
368.561.16.1	312.322	125	50	3.6	8	3.5	3.7	2
368.566.16.1	312.322	125	56	3.3	8	3.5	3.7	2
368.571.16.1	312.322	125	63	2.9	8	3.5	3.7	2
368.576.16.1	312.322	125	75	2.3	8	3.5	3.7	2
368.581.16.1	312.322	125	90	1.6	8	3.5	3.7	2
368.586.16.1	312.322	125	110	0.7	8	3.5	3.7	2
369.586.16.1	312.323	160	110	2.3	8	3.5	3.7	2
369.588.16.1	312.323	160	125	1.6	8	3.5	3.7	2
369.591.16.1	312.323	160	140	1	8	3.5	3.7	2