


Geberit PE Abzweig 88.5°



Beispielbild



TECHNISCHE DATEN

Werkstoff PE-HD

Art.-Nr.	NPX-Nr.	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 max. cm	K2 max. cm	K3 max. cm
379.158.16.1	314.211	32	32	88.5	8.5	5	3.5	3.5	2.5	1	1
360.158.16.1	314.232	40	32	88.5	13	7.5	5.5	5.5	5	2.5	2
360.159.16.1	314.212	40	40	88.5	13	7.5	5.5	5.5	4.5	2.5	2.5
361.159.16.1	314.234	50	40	88.5	15	9	6	6	6	2.5	3
361.162.16.1	314.214	50	50	88.5	15	9	6	6	5.5	2.5	2.5
363.162.16.1	314.235	56	50	88.5	17.5	10.5	7	7	7	3	3.5
363.165.16.1	314.215	56	56	88.5	17.5	10.5	7	7	6.5	3	3

Art.-Nr.	NPK-Nr.	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 max. cm	K2 max. cm	K3 max. cm
364.159.16.1	314.236	63	40	88.5	17.5	10.5	7	7	7	3	3
364.162.16.1	314.236	63	50	88.5	17.5	10.5	7	7	7	3	3.5
364.165.16.1	314.236	63	56	88.5	17.5	10.5	7	7	6.5	3	3
364.170.16.1	314.216	63	63	88.5	17.5	10.5	7	7	6	3	3
365.159.16.1	314.237	75	40	88.5	17.5	10.5	7	7	7.5	2.5	4
365.162.16.1	314.237	75	50	88.5	17.5	10.5	7	7	7	2.5	3.5
365.165.16.1	314.237	75	56	88.5	17.5	10.5	7	7	6.5	2.5	3
365.170.16.1	314.237	75	63	88.5	17.5	10.5	7	7	6	2.5	2.5
365.175.16.1	314.217	75	75	88.5	17.5	10.5	7	7	5.5	2.5	2.5
366.159.16.1	314.238	90	40	88.5	20	12	8	8	8.5	2.5	4.5
366.162.16.1	314.238	90	50	88.5	20	12	8	8	8.5	2.5	4.5
366.165.16.1	314.238	90	56	88.5	20	12	8	8	8	2.5	4
366.170.16.1	314.238	90	63	88.5	20	12	8	8	7.5	2.5	3.5

<i>Art.-Nr.</i>	<i>NPX-Nr.</i>	<i>d, ø mm</i>	<i>d1, ø mm</i>	<i>arc °</i>	<i>H cm</i>	<i>X1 cm</i>	<i>X2 cm</i>	<i>X3 cm</i>	<i>K1 max. cm</i>	<i>K2 max. cm</i>	<i>K3 max. cm</i>
366.175.16.1	314.258	90	75	88.5	20	12	8	8	7	2.5	3
366.180.16.1	314.218	90	90	88.5	20	12	8	8	6.5	2.5	2.5
367.159.16.1	314.241	110	40	88.5	22.5	13.5	9	9	10	2.5	6
367.162.16.1	314.241	110	50	88.5	22.5	13.5	9	9	9.5	2.5	5
367.165.16.1	314.241	110	56	88.5	22.5	13.5	9	9	9	2.5	4.5
367.170.16.1	314.241	110	63	88.5	22.5	13.5	9	9	9	2.5	4
367.175.16.1	314.261	110	75	88.5	22.5	13.5	9	9	8.5	2.5	3.5
367.180.16.1	314.261	110	90	88.5	22.5	13.5	9	9	7.5	2.5	3
367.185.16.1	314.221	110	110	88.5	22.5	13.5	9	9	6.5	2	2
368.162.16.1	314.242	125	50	88.5	25	15	10	10	11	2.5	6
368.165.16.1	314.242	125	56	88.5	25	15	10	10	10.5	2.5	5.5
368.170.16.1	314.242	125	63	88.5	25	15	10	10	10.5	2.5	5
368.175.16.1	314.262	125	75	88.5	25	15	10	10	10	2.5	4.5

<i>Art.-Nr.</i>	<i>NPK-Nr.</i>	<i>d, ø mm</i>	<i>d1, ø mm</i>	<i>arc °</i>	<i>H cm</i>	<i>X1 cm</i>	<i>X2 cm</i>	<i>X3 cm</i>	<i>K1 max. cm</i>	<i>K2 max. cm</i>	<i>K3 max. cm</i>
368.180.16.1	314.262	125	90	88.5	25	15	10	10	9	2.5	4
368.185.16.1	314.262	125	110	88.5	25	15	10	10	8	2	3
368.189.16.1	314.222	125	125	88.5	25	15	10	10	7	2	2
369.175.16.1	314.263	160	75	88.5	35	21	14	14	15	4.5	8
369.185.16.1	314.263	160	110	88.5	35	21	14	14	13.5	4.5	6
369.189.16.1	314.283	160	125	88.5	35	21	14	14	12.5	4.5	5
369.195.16.1	314.223	160	160	88.5	35	21	14	14	10.5	3.5	3
370.180.16.1	314.264	200	90	88.5	36	18	18	18	0	3	0
370.185.16.1	314.264	200	110	88.5	36	18	18	18	0	3	0
370.189.16.1	314.264	200	125	88.5	36	18	18	18	0	3	0
370.195.16.1	314.284	200	160	88.5	36	18	18	18	0	2	0
370.196.16.1	314.224	200	200	88.5	40	20	20	20	0	0	0
371.185.16.1	314.265	250	110	88.5	44	22	22	22	3.5	4	3.5

Art.-Nr.	NPX-Nr.	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 max. cm	K2 max. cm	K3 max. cm
371.189.16.1	314.285	250	125	88.5	44	22	22	22	3	4	3
371.195.16.1	314.285	250	160	88.5	44	22	22	22	0	3.5	0
371.196.16.1	314.285	250	200	88.5	48	24	24	24	0	0	0
371.197.16.1	314.225	250	250	88.5	48	24	24	24	0	0	0
372.185.16.1	314.266	315	110	88.5	56	28	28	28	9.5	6	9.5
372.189.16.1	314.286	315	125	88.5	56	28	28	28	9	6	9
372.195.16.1	314.286	315	160	88.5	56	28	28	28	7	6	7
372.196.16.1	314.286	315	200	88.5	56	28	28	28	4.5	0	4.5
372.197.16.1	314.286	315	250	88.5	56	28	28	28	2	0	2
372.198.16.1	314.226	315	315	88.5	56	28	28	28	0	0	0