


Geberit PE Abzweig 45°



Beispielbild



TECHNISCHE DATEN

Werkstoff PE-HD

Art-Nr.	NPK-Nr.	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 max. cm	K2 max. cm	K3 max. cm
379.108.16.1	314.111	32	32	45	10.5	3.5	7	7	2	2	2
360.108.16.1	314.132	40	32	45	13.5	4.5	9	9	3	3.5	3.5
360.109.16.1	314.112	40	40	45	13.5	4.5	9	9	2.5	3	3
361.109.16.1	314.134	50	40	45	16.5	5.5	11	11	4	4.5	4.5
361.112.16.1	314.114	50	50	45	16.5	5.5	11	11	3.5	2	2
363.112.16.1	314.135	56	50	45	18	6	12	12	4	3	3
363.115.16.1	314.115	56	56	45	18	6	12	12	4	2.5	2.5

Art.-Nr.	NPK-Nr.	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 max. cm	K2 max. cm	K3 max. cm
364.109.16.1	314.136	63	40	45	19.5	6.5	13	13	4.5	4.5	4
364.112.16.1	314.136	63	50	45	19.5	6.5	13	13	5	3	3
364.115.16.1	314.136	63	56	45	19.5	6.5	13	13	4.5	2.5	2.5
364.120.16.1	314.116	63	63	45	19.5	6.5	13	13	4	2	2
365.109.16.1	314.137	75	40	45	21	7	14	14	6.5	5	6
365.112.16.1	314.137	75	50	45	21	7	14	14	6	3	4
365.115.16.1	314.137	75	56	45	21	7	14	14	5.5	2.5	3.5
365.120.16.1	314.137	75	63	45	21	7	14	14	4.5	2.5	3.5
365.125.16.1	314.117	75	75	45	21	7	14	14	4	2.5	2.5
366.109.16.1	314.138	90	40	45	24	8	16	16	7.5	5.5	6.5
366.112.16.1	314.138	90	50	45	24	8	16	16	8	4	5
366.115.16.1	314.138	90	56	45	24	8	16	16	7.5	3.5	4.5
366.120.16.1	314.138	90	63	45	24	8	16	16	7	3	4

Art.-Nr.	NPX-Nr.	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 max. cm	K2 max. cm	K3 max. cm
366.125.16.1	314.158	90	75	45	24	8	16	16	6.5	3	3.5
366.130.16.1	314.118	90	90	45	24	8	16	16	5	2	2
367.109.16.1	314.141	110	40	45	27	9	18	18	9.5	6	7.5
367.112.16.1	314.141	110	50	45	27	9	18	18	9.5	5	5.5
367.115.16.1	314.141	110	56	45	27	9	18	18	9	4	4.5
367.120.16.1	314.141	110	63	45	27	9	18	18	8.5	3.5	4
367.125.16.1	314.161	110	75	45	27	9	18	18	7.5	3	3.5
367.130.16.1	314.161	110	90	45	27	9	18	18	6.5	2.5	3
367.135.16.1	314.121	110	110	45	27	9	18	18	5.5	2	2
368.120.16.1	314.142	125	63	45	30	10	20	20	10.5	4.5	6
368.125.16.1	314.162	125	75	45	30	10	20	20	9.5	4	5
368.130.16.1	314.162	125	90	45	30	10	20	20	8.5	3	3.5
368.135.16.1	314.162	125	110	45	30	10	20	20	7	2.5	2.5

Art.-Nr.	NPK-Nr.	d, ø mm	d1, ø mm	arc °	H cm	X1 cm	X2 cm	X3 cm	K1 max. cm	K2 max. cm	K3 max. cm
368.139.16.1	314.122	125	125	45	30	10	20	20	6	2	2
369.125.16.1	314.163	160	75	45	37.5	12.5	25	25	13.5	6.5	7.5
369.130.16.1	314.163	160	90	45	37.5	12.5	25	25	12.5	5.5	6.5
369.135.16.1	314.163	160	110	45	37.5	12.5	25	25	11	4.5	5.5
369.139.16.1	314.173	160	125	45	37.5	12.5	25	25	10	4	5
369.145.16.1	314.123	160	160	45	37.5	12.5	25	25	7.5	2.5	2.5
370.125.16.1	314.164	200	75	45	54	18	36	36	8.5	10	2.5
370.135.16.1	314.164	200	110	45	54	18	36	36	7.5	10	0
370.139.16.1	314.174	200	125	45	54	18	36	36	5.5	9	0
370.145.16.1	314.174	200	160	45	54	18	36	36	4	5.5	0
370.146.16.1	314.124	200	200	45	54	18	36	36	0	0	0
371.135.16.1	314.165	250	110	45	66	22	44	44	14	10	7.5
371.139.16.1	314.175	250	125	45	66	22	44	44	13	13	6.5

<i>Art.-Nr.</i>	<i>NPX-Nr.</i>	<i>d, ø mm</i>	<i>d1, ø mm</i>	<i>arc °</i>	<i>H cm</i>	<i>X1 cm</i>	<i>X2 cm</i>	<i>X3 cm</i>	<i>K1 max. cm</i>	<i>K2 max. cm</i>	<i>K3 max. cm</i>
371.145.16.1	314.175	250	160	45	66	22	44	44	10.5	10	0
371.146.16.1	314.175	250	200	45	66	22	44	44	7.5	0	1.5
371.147.16.1	314.125	250	250	45	66	22	44	44	4	0	0
372.135.16.1	314.166	315	110	45	84	28	56	56	23	20	16
372.139.16.1	314.176	315	125	45	84	28	56	56	21.5	20	14.5
372.145.16.1	314.176	315	160	45	84	28	56	56	19.5	17.5	12.5
372.146.16.1	314.176	315	200	45	84	28	56	56	16.5	5	10
372.147.16.1	314.176	315	250	45	84	28	56	56	13	5.5	6.5
372.148.16.1	314.126	315	315	45	84	28	56	56	8.5	2	2